

QoS of network infrastructure in a wireless sensor system for real-time measurement pH parameter of fishery

by Muhammad Imam Ghozali

Submission date: 29-Jun-2020 08:20PM (UTC+0700)

Submission ID: 1351328086

File name: Ghozali_2020_J._Phys.__Conf._Ser._1524_012108.pdf (1.1M)

Word count: 2309

Character count: 12619


PAPER • OPEN ACCESS

QoS of network infrastructure in a wireless sensor system for real-time measurement pH parameter of fishery

1

To cite this article: M I Ghozali *et al* 2020 *J. Phys.: Conf. Ser.* **1524** 012108

View the [article online](#) for updates and enhancements.



IOP | ebooks™

Bringing together innovative digital publishing with leading authors from the global scientific community.

Start exploring the collection—download the first chapter of every title for free.

QoS of network infrastructure in a wireless sensor system for real-time measurement pH parameter of fishery

M I Ghozali¹, W H Sugiharto¹, H Susanto², M A Budihardjo³, S Suryono⁴

¹ Department of Informatics Engineering, Faculty of Engineering, UniversitasMuria Kudus, Kudus-Indonesia

²Department of Chemical Department of Chemical Engineering, Universitas Diponegoro, Semarang, Indonesia

³Department of Environmental Engineering, Faculty of Engineering, Diponegoro University, Semarang-Indonesia

⁴Physics Department of Science and Mathematics Faculty, Diponegoro University, Semarang-Indonesia

Corresponding author: imam.ghozali@umk.ac.id

Abstract. The problem of mass fish mortality in Indonesia is already common and generally occurs. Environmental conditions determine the survival of fish. Acidity (pH) is one of the important things in determining the water quality of water. real-time information about pH water is important to avoid the danger of mass fish dies because of unhandled water pH. *Network Infrastructure* devices comprise those devices that facilitate the movement of data along with the communication media. the difference between the station distance and the wireless access point does not affect the change in the bitrate of each station QoS measurements based on data distribution delay. Shows that if the wireless sensor's connectivity in sending data acquisition pH from the node station to the web service, Delay data transmission affects the accuracy of the measurement and presentation of data on the cloud server.

1. Introduction

The total area of Indonesia is 7.81 million km² which consists of 2.01 million km² of land, 3.25 million km² of the sea, and 2.55 million km² of the Exclusive Economic Zone (EEZ). Indonesia became a country with a greater water area than the land area, therefore Indonesia is referred to as the Maritime State. Indonesia is the second-largest producer of marine fisheries in the world, after China. Indonesian society in 2017 experienced an increase in fish consumption. From these data the total Indonesian fish consumption of an average of 20-31.4 kg/cap (moderate), in recent years even tends to increase 31.4 kg/cap-height. With consumption increasing every year, meeting the needs of fisheries production becomes important [1].

From 2011 to 2016 fisheries production in Indonesia has increased both from capture fisheries and aquaculture production, where aquaculture production is greater than capture fisheries. For example, in 2016 capture fisheries production was 6.83 million tons while aquaculture production was 16.68 million tons, the range of margin data is the basis for opportunities to open new land for fish conservation for Indonesian people. Starting in 2014 - 2017 the area of conservation areas has always increased, from 16.4 million hectares in 2014 to 19.14 million hectares in 2017[1].



Content from this work may be used under the terms of the [Creative Commons Attribution 3.0 licence](https://creativecommons.org/licenses/by/3.0/). Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

Unfortunately, the problem of mass fish mortality in Indonesia is already common and generally occurs [2], for example, November 30th, 2015 more than 650 kg fishes found dead in the coast of Ancol-Jakarta[3], March 2010dmore than 1.150-ton fishes found dead inManjau Lake -West Sumatera 1.150 [4]. Environmental conditions determine the survival of fish. Determination of water environmental conditions has water parameters including water (depth, brightness, water temperature, acidity (pH), dissolved oxygen (DO) and ORP (Oxidation Reduction Potential)). Acidity (pH) is one of the important things in determining the water quality of water. real-time information of pH water is important to avoid the danger of mass fish dies because of unhandled water pH.pH indicates how acidic or basic a substance is. H refers to the number of hydrogen ions and hydroxide ions present in substances; these hydrogen ions affect the nature of a substance. Some fish species have different pH levels. Wireless sensor network activities include several aspects of data traffic including receiving, sending and processing data[5], this wireless sensor network can be used to monitor pH in real-time. The development of wireless sensor networks has begun to develop in various aspects of life including the environment[6], natural disasters [7], medical health [8], agriculture [9], transportation [10], industry [11] and smart city [12].

Performance of the wireless sensor system is strongly influenced by the network infrastructure, errors in infrastructure can have an impact on the failure of sending data to the wireless sensor, so information cannot be conveyed in real-time. QoS can be defined as well as the ability to provide performance guarantees on the network. The performance of the wireless sensor system can be seen based on QoS measurement parameters including Packet Loss, Delay (Latency), Jitter, and Throughput [13].

When the network infrastructure is built the next challenge is maintenance to ensure the network running well, unfortunately, stable Quality of Service (QoS) requirements become an interesting problem because of heterogeneous data traffic flows, dynamic network conditions, and resource-limited nature of sensor nodes [8].

The development of the Wireless Sensor Network communication system is usually using multi-hop communication design, more routing loops used in the wireless sensor system will affect the sensor data distribution [14]. The real-time performance of the communication data in the wireless sensor system to the router requires a stable quality of service (QoS) [15][16]. This paper purpose to measure the QoS in the design of wireless sensor network infrastructure to maintain the performance of the network to deliver real-time data.

2. Method

2.1. Wireless sensor system

Wireless sensor network technology has been emerging as a viable solution to many innovative applications [17]. The Wireless Sensor Network consists of several sensors distributed randomly to measure physical parameters of the environment and transmit readings from these sensors wirelessly to the central station. The application of wireless sensors is being widely applied in environmental surveillance [18]because the wireless sensor network is a technology developed to collect data in real-time [19].

2.2. QoS

Quality of service comprises requirements on all the aspects of a connection, such as service response time, loss, signal-to-noise ratio, crosstalk, echo, interrupts, frequency response, loudness levels, and so on. A subset of telephony QoS is a grade of service (QoS) requirements, which comprises aspects of a connection relating to capacity and coverage of a network, for example, guaranteed maximum blocking probability and outage probability.

QoS is sometimes used as a quality measure, with many alternative definitions, rather than referring to the ability to reserve resources. Quality of service sometimes refers to the level of quality of service, i.e. the guaranteed service quality. High QoS is often confused with a high level of performance, for example, high bit rate, high latency and low bit error rate [5].

2.3. Network infrastructure

Network Infrastructure comprises those devices that facilitate the movement of data along with the communication media[20]. A link is a communication path between two nodes. The terms " circuit " and " Channel " are frequently used as synonyms for the link. There are different types of topologies like bus, ring, tree, mesh etc. However, we will consider five basic network structures-topology [21]. Therefore, it is necessary to build the right network topology without obstacles to collect geologically distributed data quickly and move it to the data center for subsequent processing [22].

Network topology without using a router when QoS analysis shows packet loss during data distribution, after the addition of a router results in a decrease in packet loss during data distribution [23]. Figure 1 shows the router hardware and Figure 2 shows the access point hardware to build the infrastructure of the wireless sensor network.



Figure 1. Router Hardware



Figure 2. Access point hardware

3. Network infrastructure for wireless sensor design

Figure 3 shows the design of infrastructure network realtime pH acquisition, this design involves the multiple node station. The node station has a pH sensor to collect pH value in the monitoring area. Each node station connects into the wireless access point in the monitoring area. Router gateway manages the transmission data between access point and internet service provider. The data then sent into the cloud computing server and represent real-time data acquisition from the node station. Figure 4 shows real-time online data is present with a web-based online application.




Figure 3.Real-time infrastructure data acquisition



Figure 4.Implementation of Network Infrastructure For Wireless Sensor

4. Result and discussion

4.1. Implementation of network infrastructure for wireless sensor

Node Station is equipped pH sensor and wireless device to connect into an access point its show in Figure 5 and Figure 6. The Figure shows the access point connected into the router gateway that's served internet connection by Internet service protocol. Realtime web-based online application for pH sensor its show in Figure 7, that's the application present the multiple data from each node station.




Figure 5. Node station



Figure 6. Wireless connection on a node station




Figure 7. Real-time pH data acquisition website on cloud computing server

4.2. QoS of network infrastructure for wireless sensor

The results of the measurement of delay can be seen that the delay of each station changes, where the difference between the station distance and the wireless access point does not affect the change in the bitrate of each station. What matters is the greater the bitrate value, the smaller the delay that occurs. This condition occurs because when the bitrate that is transmitted is large, the data transfer process will become faster. So the time needed for the data to arrive is faster.

Table 1 QoS measurement of delay and bitrate each station

Station	Distance (km)	Bitrate	Delay (bit)
1	2	220	0.04
2	5	199	0.08
3	10	155	0.08
4	15	120	0.15
5	20	96	0.27
6	30	77	0.25

5. Conclusion

Based on QoS measurements based on data distribution delay in table 1. Shows that if the wireless sensor's connectivity in sending data acquisition pH from the node station to the web service, Delay data transmission affects the accuracy of the measurement and presentation of data on the cloud server.

Acknowledgment

This research is funded by the Directorate of research and community services Directorate General of Strengthening Research and Development Ministry of Research, technology and higher education in accordance with the letter of the contract Research Number: 86./LPPM.UMK/B.09.55/V/201.

References

- [1] Kementerian Kelautan dan Perikanan 2018 Produktivitas Perikanan Indonesia, Kementerian Kelautan Dan Perikanan produktivitas Perikanan Indonesia pada: Forum Merdeka Barat 9 Kementerian Komunikasi Dan Informatika *Forum Merdeka Barat 9 Kementerian Komun. Dan Inform.*
- [2] Syofyan I, Usman dan Nasution P 2011 *Studi Kualitas Air Untuk Kesehatan Ikan Dalam Budidaya Perikanan Pada Aliran Sungai Kampar Kiri* vol. 1 no. April pp. 64–70
- [3] Putri M R A, Hartati S T, and Satria F 2016 *Bawal Widya Ris. Perikan. Tangkap* vol. 8 no. 2 pp. 77–90
- [4] Nasution Z, Sari Y D, and Huda H M 2011 *J. Kebijak. Sos. Ekon. Kelaut. dan Perikan.* vol. 1 no. 1 pp. 19–31
- [5] Zhou M and Ma Y 2013 *J. China Univ. Posts Telecommun.*
- [6] Ransing R S and Rajput M 2015 *ICNTE Proceedings*
- [7] Islam R U, Andersson K, and Hossain M S 2017 *IEEE Conference on Computer Communications Workshops INFOCOM WKSHPs*
- [8] Kaur T and Kumar D 2019 *Wirel. Networks*
- [9] Muangprathub J, Boonnam N, Kajornkasirat S, N Lekbangpong, A Wanichsombat and P Nillaor 2019 *Comput. Electron. Agric.*
- [10] Azpilicueta L *et al.* 2015 *IEEE Trans. Intell. Transp. Syst.*
- [11] Faheem M and Gungor V C 2018 *Appl. Soft Comput. J.*
- [12] Al-Turjman F 2018 *Comput. Commun.*
- [13] Sugeng W, Istiyanto J E, Mustofa K and Ashari A 2015 *Int. J. Comput. Networks Commun. Secur.* vol. 3 no. 2 pp. 48–53
- [14] Adi P D P and Kitagawa A 2019 *Int. J. Adv. Comput. Sci. Appl.*
- [15] Wu F, Rüdiger C and Yuce M R 2017 Real-time performance of a self-powered environmental IoT sensor network system *Sensors (Switzerland)*
- [16] Akerele M, I Al-Anbagi and M Erol-Kantarci 2019 *IEEE Access*
- [17] Ferdoush S and X Li 2014 *Procedia Comput. Sci.* vol. 34 pp. 103–110
- [18] Ozdemir S 2009 Data aggregation in wireless sensor networks in *RFID and Sensor Networks: Architectures, Protocols, Security and Integrations*
- [19] El-Sayed B, N Farra, N Moacdieh, H Hajj, R Haidar and Z Hajj 2011 *MECBME*
- [20] Norman T 2016 Information Technology Systems Infrastructure in *Effective Physical Security: Fifth Edition*
- [21] Pandya K 2013 Network Structure or Topology *Netw. Struct. or Topol.*
- [22] Yi X, F Liu, J Liu and H Jin 2014 *IEEE Netw.*
- [23] Nindiyasari R, Murti A C and Ghazali M I 2019 *Netw. Eng. Res. Oper.*

QoS of network infrastructure in a wireless sensor system for real-time measurement pH parameter of fishery

ORIGINALITY REPORT

14%

SIMILARITY INDEX

12%

INTERNET SOURCES

9%

PUBLICATIONS

14%

STUDENT PAPERS

PRIMARY SOURCES

1

Submitted to Universitas Negeri Jakarta

Student Paper

8%

2

www.eutests.eu

Internet Source

6%

Exclude quotes On

Exclude matches < 3%

Exclude bibliography On



Kudus, 30 Juni 2020

Kopi UPT Perpustakaan UMK

Noor Athiyah, S.S., M.Hum.